

Determination of the electrical conductivity and the electroosmotic transfer in the concentrated dispersions on the basis of the cell theory of the electroosmosis

D.L.Gulo and O.L.Alexejev

*F.D.Ovcharenko Institute of Biocolloidal Chemistry , National Academy of Sciences of Ukraine,
42 Vernadsky blvd ., 252142 Kyiv , Ukraine
(February 1, 2008)*

Theoretical calculations of the electrical conductivity and electroosmotic transfer as functions of the disperse phase volume fraction and non-dissolving boundary layer thickness were provided on the basis of the cell theory of electroosmosis for the limiting case of large degree of electric double layers' overlapping in interparticle space . The obtained results are in qualitative agreement with the experimental data and describe the main features of the latter .

PACS number:61.65.50+m.66

I. INTRODUCTION

The obtaining of equations , which can accurately describe electrokinetic phenomena in concentrated dispersions , is impeded by a series of causes . The influence of the interaction between equilibrium and polarization fields of colloid particles becomes considerable . The properties of disperse medium are also changed by the surface of solid phase . Liquid layers being near the surface and having peculiar properties occupy a substantial volume part of a concentrated dispersion threshold space and strongly influence the electrokinetic phenomena .Systematic investigations of the electrokinetic phenomena in the systems of colloidal dispersity led to the discovery of regularities [1- 3] which initiated the elaboration of the electroosmosis theory in plane capillaries for the limiting case of large degree of electric double layers' overlapping [4] . Unlike the previous work [5] , the model of the near wall layer of fluid in which it combined the non - dissolving volume properties with the hydrodynamic mobility was developed and this gave a theoretical explanation for many experimental results . The continuation of investigations in this field was the construction of the cell theory of the electroosmosis [6] where the cell model widely applied while solving hydrodynamic tasks [7] was used to electrokinetic problems . The present paper contains theoretical calculations of the conductivity and electroosmotic transfer as functions of disperse phase volume fraction for experimentally investigated systems and the comparison of obtained calculations with the experimental data .

II. STATEMENT AND SOLUTION OF A TASK

In the cell model a single particle (radius a) is considered to be surrounded by a sphere of such a size (radius c) that the fraction of liquid within the sphere is the same as the porosity of the colloid system . Suspension is considered as the aggregate of these typical structural units. Having designated the volume particle fraction in the suspension by ϕ , we obtain :

$$\phi = a^3/c^3. \quad (1)$$

Having designated the radius of the dissolving and non - dissolving layer in the cell by b , the thickness of the non - dissolving boundary layer h is :

$$h = b - a, \quad (2)$$

(see Fig.1). In the work [6] for the calculation of the electroosmosis rate of the 1 - 1 binary electrolyte the following equation system was solved :

$$-\eta \operatorname{rot} \operatorname{rot} \vec{v} - \operatorname{grad} (p + RT\gamma^+ \mu^+ + RT\gamma^- \mu^-) = 0, \quad (3)$$

$$\operatorname{div} \vec{v} = 0, \quad (4)$$

$$\operatorname{div} \operatorname{grad} \mu^\pm = 0, \quad (5)$$

where η is the fluid viscosity, p is the pressure, ν is the fluid rate, μ are dimensionless (in the RT units) electrochemical ion potentials, C are their concentrations. In this case $\gamma^\pm = C - C_o$, C_o is the concentration of the equilibrium solution of the electrolyte. The general solutions were given by the equations :

$$\mu^\pm = \cos \theta (A_1^\pm r + A_2^\pm r^{-2}), \quad (6)$$

$$\nu_r = \cos \theta (B_1 - \frac{2B_2}{r^3} + \frac{B_3 r^2}{10} + \frac{B_4}{r}), \quad (7)$$

$$\nu_\theta = -\sin \theta (B_1 + \frac{B_2}{r^3} + \frac{B_3 r^2}{5} + \frac{B_4}{2r}), \quad (8)$$

$$p = \frac{\eta \cos \theta}{a} (B_3 r + \frac{B_4}{r^2}). \quad (9)$$

A substitution of these general equations in the edge conditions of system (3 - 5) (taking into account other conditions characterizing the electroosmosis process) enables to obtain values of the fluid rate I_v , electrochemical ion potentials $\mu^\pm$, the average electric field E , the electroosmotic transfer P_e and the conductivity K_Σ (I_E is the electric current , F is the Faraday constant):

$$I_V = \frac{\nu_r}{\cos \theta} \Big|_{r=c}, \quad (10)$$

$$E = \frac{RT}{Fc \cos \theta} (\mu^+ - \mu^-) \Big|_{r=c}. \quad (11)$$

$$P_e = I_V / I_E, \quad (12)$$

$$K_\Sigma = I_E / E. \quad (13)$$

(13) The edge problem is reduced to 12 linear algebraic equations by a substitution of the general solutions (6 - 9) into the edge conditions of the system (3 - 5) (taking into account other conditions characterizing the electroosmosis process). In the present paper the determination of values of the liquid velocity ν and electrochemical potentials $\mu^\pm$ was provided by solving this system of equations . The Gauss numerical method ,which is classified as direct , was used for the solution , taking into consideration relatively low order of the determinant [8]. The brief algorithm of the system solution is described below :

- 1.Input N - the order of the equations system
- 2.Formation of the augmented matrix A (N , N+1)
- 3.Gauss method
- 4.Output of the solution X (N)

Parameters for the problem solution were taken from the work [9] in which dispersion of synthetic diamond in HCl solution was investigated . Calculations of P_e and K_Σ were provided for the suspension with particle radius $a = 0.15 \cdot 10^{-6}$ m , surface charge density $kju = 0.55 \cdot 10^{-6}$ C/cm² , electrolyte concentration $C_0 = 10^{-5}$ mole/l HCl . The calculation results of the electroosmotic transfer P_e and the conductivity K_Σ as functions of the volume particle fraction ϕ are given on Fig.2-3. P_e was calculated for different non-dissolving boundary layer thicknesses $h = 1$ nm and $h = 10$ nm . The experimental dependencies of P_e and K_Σ for the same values of particle radius a , electrolyte concentration C_0 , surface charge density Kju and volume particle fraction ϕ are given on these figures too .

III. DISCUSSION

The dependence of the electroosmotic transfer P_e on the volume particle fraction ϕ which was determined on the basis of the cell theory of the electroosmosis shows the correspondence to the experimental regularity . The increase of charged particle concentration in the suspension results in the increase of the degree of particle diffuse double layers' overlapping and the augment of counterion concentration in the porous space. Thus , the electroosmotic transfer

diminishes with the volume particle fraction increase . Theoretically obtained function $P_e(\phi^{-1})$ (Fig.2 , line 1 for $h = 1$ nm , line 2 for $h = 10$ nm) is linear which is typical for the electroosmosis in concentrated disperse systems . The increase of the non- dissolving boundary layer thickness leads to the decrease (in these conditions) of P_e which is confirmed by the experiment (Fig.2 , lines 3 , 4) . The calculations of diamond particles dispersion conductivity K_Σ versus the volume particle fraction ϕ are shown on Fig.3 . Line 1 corresponds to experimental data , line 2 does to theoretical ones . In this case , when the electrolyte concentration is low and values of volume particle fraction are high , the effect of specific surface conductivity is significant . The resistance increase due to the increase of the insulating particle concentration is compensated and the conductivity of suspension is growing with the volume particle fraction augment (so called capillary superconductivity [10]). The calculation results (accordingly the cell theory of the electroosmosis) show the correspondence to and describe the main features of the experimental data : linear dependence of $P_e(\phi^{-1})$, the electroosmotic transfer increase with the decrease of the non-dissolving boundary layer thickness , character of dependencies K_Σ on ϕ . The quantitative description of real disperse systems is impeded by a series of cases such as presence of particles of different sizes , deviation of particle shape from spherical , influence of specific surface conductivity . More detailed investigations of concentrated suspensions' properties using the model systems which have more definite physical and chemical parameters are the subjects of future work .

ACKNOWLEDGMENTS

The authors are grateful to Zharkih N. and Shilov V. for useful conversations .

-
- [1] Alexejev O., Ovcharenko F ., Bojko Y., Procenko I.: Colloid . Zhurn ., 36 , 121 (1974) .
 - [2] Alexejev O., Ovcharenko F ., Bojko Y ., Chubirka L .: Doklady AN SSSR , 244 , 1415 (1979) .
 - [3] Alexejev O., Ovcharenko F ., Bojko Y.: Colloidn . Zhurn . , 37 , 835 (1975) .
 - [4] Duhin S., Shilov V.: In book :” Uspehi colloidnoj himii” , Kiev , p. 96 (1983) .
 - [5] Churaev N., Deryagin B.: Colloid. Zhurn., 38 ,751 (1966) .
 - [6] Shilov V., Zharkih N.: Cond - mat / 9812295 (1999).
 - [7] Happel J., Brenner H.: In book :” Low Reynolds number hydrodynamics” , p. 447 (1965) .
 - [8] Forsythe J.: In book :” Numerical calculations on personal computers” , New York , (1978) .
 - [9] Alexejev O., Ovcharenko F ., Bojko Y ., Shilov V .: Colloid. Zhurn., 50 , 211 ,(1988) .
 - [10] Fridrihsberg A.: In book :” Kurs colloidnoi himii” , Leningrad , p.213 (1984) .

FIG. 1. Structural elements in the cell model of a disperse system. a -radius of a particle; h -thickness of the non-dissolving layer; b -radius of the non-dissolving layer in the cell; c -cell radius; σ -particle surface charge ; 2 -external boundary of the non-dissolving layer; 3 -external boundary of a diffuse layer.

FIG. 2. Dependencies of the electroosmotic transfer P_e on the reciprocal volume particle fraction j . 1 -theoretical values for the non-dissolving boundary layer thickness $h = 1$ nm; 2 -theoretical values for the non-dissolving boundary layer thickness $h = 10$ nm; 3 -experimental data for system "diamond - HCL " in the presence of the saccharose solution which destructs the non-dissolving boundary layer; 4 -experimental data for system "diamond - HCL " without the saccharose solution.

FIG. 3. Dependence of the electrical conductivity K_{Σ} on the volume particle fraction j . 1 -experimental data for system "diamond - HCL "; 2 -theoretical values.

This figure "fig2.gif" is available in "gif" format from:

<http://arXiv.org/ps/cond-mat/9903201v1>

This figure "fig3.gif" is available in "gif" format from:

<http://arXiv.org/ps/cond-mat/9903201v1>